



OKS 2901 - Product Information

Fields of Application:

Increases tensile force by up to 50 % for all kinds of V-belts, round and flat belts on fans, compressors, pumps, ventilators, mills etc. Protects against drying out and wear, prevents belt squeaking and slip.

OKS 2901 Belt Tuning, Spray



Advantages and Benefits:

Clean, light-coloured film for increasing tensile strength and car of many kinds of belts.

Application:

For optimum results clean belt carefully, best way is to clean mechanically first and then with Universal Cleaner OKS 2610/2611. Spray evenly on the belt. Let product take effect for approx. 30 min. before use. If necessary, repeat application. Belts made of SBR and CR are not compatible to OKS 2901. For further questions please contact our Technical Department.

Additional Information:

Packaging (Article number):
- 400 ml Spray (02901004)

Version:
E-11.1/05

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 2901 Belt Tuning, Spray

Technical Data

	Norm	Conditions	Unit	Value
Base Oil				
Type				Adhesive oil
Additives				
Solvent				Special boiling point gasoline
Application Data				
Density	DIN 51 757	+20°C, aktive agent	g/ml	0,74
Colour				yellowish
Application Temperature				
Maximum application temperature			°C	80

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark