



OKS 2801 – Product Information

OKS 2801 Leak Detector, Spray



Fields of Application:

Detection of leaks in pressurised piping and containers, e.g. on compressors, steel bottles, fittings, shut-off valves, breathing devices, oxyacetylene gas and inert-gas arc welding devices, Bunsen burners, valves, screw fittings of compressed-air lines etc. Suitable for compressed air, refrigerant, acetylene, butane, natural gas, carbon dioxide, gaseous oxygen, propane, town gas, nitrogen, hydrogen, and ammonia.

Advantages and Benefits:

Best suitability to detect even smallest leaks which are immediately visualized by immediate formation of bubbles at the leaking spot. Saves energy and warns of gas loss. No corrosive effects. DVGW approved.

Application:

Spray from distance onto the area to be checked, a formation of bubbles indicates a leakage. Clean with water after the application on plastic parts to prevent stress cracks. For additional questions please contact our technical department.

Additional Information:

Packaging:
- 400 ml Spray

Version:
E-01.1/14

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 2801 Leak Detector, Spray

Technical Data

	Norm	Conditions	Unit	Value
Base				
Type				Water
Additives				
Additives				Corrosion protection active substances
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	1,0
Colour				transparent
Service Temperatures				
Minimum service temperature			°C	0
Maximum service temperature			°C	50
Releases/Specifications				
DVGW	DIN EN 14291		Reg.-No.	NG-5170AO0659

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark