



OKS 621 - Product Information

Fields of Application:

High-performance rust remover for fast and nondestructive disassembly of extremely seized-up parts or bolts, e.g. for vehicles, agricultural or construction machinery, vessels and port facilities; also for all machinery in industry and trade.

OKS 621 (F)Rust Breaker



Advantages and Benefits:

The solvent contained in OKS 621 cools down the assembled parts/screws rapidly to -40°C. This results in a slight shrinkage of the affected profile. Capillary cracks in the corrosion layer appear, allowing an easier penetration of the creeping oil. Contrary to a heat treatment of seized-up bolts OKS 621 does not cause heating damages in the environment. No damages through overheating. OKS 621 is resin and acid-free. Without silicone.

Application:

Clean components from dirt. Shake well before use. Spray from a distance of 10 – 15 cm on to the parts/screws and allow OKS 621 to react for 1 – 2 min. Repeat treatment if necessary. For additional questions please contact our technical department.

Additional Information:

Packaging (article number):
- 400 ml Spray (00621004)

Version:
E-05.01/04

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 621 (F)Rust Breaker

Technical Data

	Norm	Conditions	Unit	Value
Base oil				
Type				mineral oil + solvents
Application data				
Colour				light-coloured
Service temperatures				
Minimum			°C	-10
Maximum			°C	+40

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark